

QUICKE dla CLAAS od 30.12.2008

Ładowacze III-sekcyjne, sterowane przy pomocy Joysticka z akumulatorem hydr.-gazowym (pochłaniacz drgań)

Wysokość unoszenia - poziom osprzętu	2.95	3.25	3.50	3.75	4.00	4.25	4.50	2.95	3.25	3.50	3.75	4.00
Udźwig 80 cm od osi obrotu na max. wys.	1.150	1.200	1.550	1.700	2.000	2.100	2.250	950	1.150	1.450	1.600	1.850
Model ciągnika	Q25	Q35	Q45	Q55	Q65	Q75	Q85	Q20	Q30	Q40	Q50	Q60
ARES 546, 556, 566, 557, 567, 577			X	X						X	X	
ARES 616, 626, 636, 656, 696,				X	X						X	X
ARES 617, 657, 697				X	X						X	X
ARES 816, 826, 836 RZ						X						
Arion : 410, 420, 430			X	X						X	X	
Arion CIS: 510, 520, 530, 540			X	X						X	X	
Arion CEBIS: 510, 520, 530, 540			X	X						X	X	
Arion 610, 620, 630, 640				X	X						X	X
AXION 810, 820, 830, 840, 850 *						X						
Axos 310, 320, 330, 340			X	X						X	X	
CELTIS 426, 436, 446, 456			X	X						X	X	
Nectis VL 217, 227, 237, 257,	X	X						X	X			
Nectis F 227, 247, 257,	X	X						X	X			