

QUICKE dla FENDT

Wysokość unoszenia - poziom osprzętu	2.95	3.25	3.50	3.75	4.00	4.25	4.50	2.95	3.25	3.50	3.75	4.00
Udźwig 80 cm od osi obrotu na max. wys.	1.150	1.200	1.550	1.700	2.000	2.100	2.250	950	1.150	1.450	1.600	1.850
Model ciągnika	Q25	Q35	Q45	Q55	Q65	Q75	Q85	Q20	Q30	Q40	Q50	Q60
206 - 209 S und P	x	x						x	x			
307, 308, 309 CI			x	x						x	x	
Farmer 309, 310, 311, 312 Vario			x	x						x	x	
Farmer 409, 410, 411, 412, 413 Vario				x							x	
Farmer 414, 415 Vario					x							x
Farmer 711, 712 Vario				x	x						x	x
Farmer 714, 716, 815, 817 Vario					x	x						
Farmer 718, 817, 818, 820 Vario						x						x
916, 920, 924, 926, 930 Vario MAN Motor							x					x
Fendt Adapter 300-500 Baureihe 4 Zylinder			x	x						x	x	
Fendt Adapter 300-500 Baureihe 6 Zylinder				x	x						x	x
800 Baureihe						x						
Favorit 611-615 LSA					x	x						
ZAPINANIE SWORZNIOWE	Q25	Q35	Q45	Q55	Q65	Q75	Q85	Q20	Q30	Q40	Q50	Q60
Farmer 240 - 260 S SA	x	x						x	x			
Farmer 275 - 280 S SA		x	x						x	x		
Farmer 304 - 310 LS / LSA		x	x						x	x		
Farmer 311 - 312 LS / LSA				x							x	
Favorit 509 - 510 C				x							x	
Favorit 511 - 514 C				x							x	
365 - 380 GTA			x							x		