

QUICKE dla John Deere

Wysokość unoszenia - poziom osprzętu	2.95	3.25	3.50	3.75	4.00	4.25	4.50	2.95	3.25	3.50	3.75	4.00
Udźwig 80 cm od osi obrotu na max. wys.	1.150	1.200	1.550	1.700	2.000	2.100	2.250	950	1.150	1.450	1.600	1.850
Model ciągnika	Q25	Q35	Q45	Q55	Q65	Q75	Q85	Q20	Q30	Q40	Q50	Q60
5620, 5720, 5820		x	x	x						x	x	
6010, 6100, 6110, 6200, 6210			x	x							x	
6120, 6220			x	x							x	
6300, 6310, 6400, 6410			x	x	x						x	x
6320, 6420			x	x	x						x	x
6230, 6330, 6430				x	x						x	x
6530, 6630				x	x							x
6830, 6930					x	x						x
6500, 6506, 6510, 6600, 6610,				x	x	x						x
6800, 6810, 6900, 6910				x	x	x						x
6520, 6620, 6820, 6920, 6820 TLS, 6920 TLS				x	x	x						x
6520 TLS, 6620 TLS				x	x	x						x
7430, 7530						x						x
7600, 7610, 7700, 7710, 7800, 7810						x						
7720, 7820, 7920							x					
7730, 7830, 7930							x					
3200 - 3210, 3300 - 3310, 3400 - 3410		x	x							x		
5215 - 5315, 5415 - 5515	x	x						x	x			
ZAPINANIE SWORZNIOWE	Q25	Q35	Q45	Q55	Q65	Q75	Q85	Q20	Q30	Q40	Q50	Q60
5200, 5300, 5400, 5500, 5210,	x	x	x					x	x	x		
5310, 5410, 5510	x	x	x					x	x	x		
5220, 5320, 5420, 5520	x	x	x					x	x	x		
1750, 1850, 1950 MC 1, CC2, SG2		x							x			
1040, 1140 MC 1, SG2 OPU		x	x						x	x		
1640 MC1, SG2, XE		x	x						x	x		
2040, 2140, LPU, XC1, XE, SG2			x	x						x	x	
2250, 2450, 2650, 2850, MC1, CC2, SG2			x	x						x	x	
3040, 3050, 3140, 3350, 3640, 3650 XE, SG2				x							x	
4050, 4055, 4250, 4255					x	x						x