

QUICKE dla LAMBORGHINI

Wysokość unoszenia - poziom osprzętu	2.95	3.25	3.50	3.75	4.00	4.25	4.50	2.95	3.25	3.50	3.75	4.00
Udźwig 80 cm od osi obrotu na max. wys.	1.150	1.200	1.550	1.700	2.000	2.100	2.250	950	1.150	1.450	1.600	1.850
Model ciągnika	Q25	Q35	Q45	Q55	Q65	Q75	Q85	Q20	Q30	Q40	Q50	Q60
R6 130S, 140S, 150S, 165S					x	x					x	
150.7, 165.7 R6 VRT 150.7, 165.7					x	x					x	x
R6 180.7 *						x					x	x
R6 100, 120 Standard				x	x						x	x
R6 110 Standard				x	x						x	x
R6 100, 120 + Highprofile *				x	x						x	x
R6 110 + Highprofile *				x	x						x	x
R5 115, 130				x	x						x	x
R 4.105			x	x	x					x	x	x
R 4.85, 4.95, 4.110			x	x						x	x	
R 3.75		x							x			
R 3.85, 3.95, R3 EVO 85, 100		x	x						x	x		
R 2.56, R 2.66 + E Target	x	x						x	x			
R 2.76, R 2.86 + E Target	x	x						x	x			
R 3.85 T, 3.95 T		x	x						x	x		
R8 215 / 265							x					
Crono Target 55, 70	x							x				
Grand Prix 874-90, Prix Target 95		x	x						x	x		
Grand Prix 674-70, Prix Target 75		x	x						x	x		
Grand Prix 774-80		x	x						x	x		
Premium 850, 950, 1050			x	x						x	x	
Premium 1060, 1100, 1300				x	x	x					x	x
ZAPINANIE SWORZNIOWE	Q25	Q35	Q45	Q55	Q65	Q75	Q85	Q20	Q30	Q40	Q50	Q60
105 Formula			x	x						x	x	
550, 600, 660, 700 554-50		x	x						x	x		
564-60 Chrono, 574-60 N Cross, 574-70		x	x						x	x		
664-60, 664-55,		x	x						x	x		
664-65 Sprint, 674-70 N Cross		x	x						x	x		
674-70 GP, 674-70		x	x						x	x		
674-75 Sprint, 684-85 Sprint		x	x						x	x		

Wysokość unoszenia - poziom osprzętu	2.95	3.25	3.50	3.75	4.00	4.25	4.50	2.95	3.25	3.50	3.75	4.00
Udźwig 80 cm od osi obrotu na max. wys.	1.150	1.200	1.550	1.700	2.000	2.100	2.250	950	1.150	1.450	1.600	1.850
ZAPINANIE SWORZNIOWE	Q25	Q35	Q45	Q55	Q65	Q75	Q85	Q20	Q30	Q40	Q50	Q60
774-80 N + LP Cross, 774-80 + GP		x	x						x	x		
775, 660 F		x	x						x	x		