

QUICKE dla LANDINI

Wysokość unoszenia - poziom osprzętu	2.95	3.25	3.50	3.75	4.00	4.25	4.50	2.95	3.25	3.50	3.75	4.00
Udźwig 80 cm od osi obrotu na max. wys.	1.150	1.200	1.550	1.700	2.000	2.100	2.250	950	1.150	1.450	1.600	1.850
Model ciągnika	Q25	Q35	Q45	Q55	Q65	Q75	Q85	Q20	Q30	Q40	Q50	Q60
Rex 75 , 85, 95, 105 F / GE und GT	x							x				
Legend 115, 120, 125, 130, 135				x	x	x					x	x
Legend 140, 145, 160, 165, 180, 185					x	x						x
Mythos 105 (90 - 100)			x	x						x	x	
Mythos 115				x	x						x	x
Powerfarm 60	x							x				
Powerfarm 75, 85, 95, 105		x	x						x	x		
Vision 80, 85		x	x						x	x		
Vision 90, 95, 100, 105			x	x						x	x	
Alpine	x	x						x	x			
Landpower 125, 135				x	x	x						x
Landpower 125, 135 Tier 3 Motor				x	x	x						x
Landpower 145, 165, 185					x	x						x
Landpower 145, 165, 180 Tier 3 Motor					x	x						x
Powermaster 180, 200, 220							x					
Powermaster 190, 210, 230 Tier 3 Motor												x
Power Max 145-165					x	x						
Technofarm 55, 65, 75, 80	x	x						x	x			
ZAPINANIE SWORZNIOWE	Q25	Q35	Q45	Q55	Q65	Q75	Q85	Q20	Q30	Q40	Q50	Q60
Atlas 70, 75, 80, 85		x	x						x	x		
Atlas 90 Turbo		x	x						x	x		
Advantage 65, 75, 85		x	x						x	x		
Blizzard 50, 60, 65, 75	x	x						x	x			
Blizzard 85, 95			x	x					x	x		
Ghibili 80, 90, 100			x	x					x	x		
Globus 55, 60, 65, 70, 75, 80	x	x						x	x			
Mytos 90, 100, 110			x	x						x	x	
Alpine 65, 75, 85 STD, Sherpa			x	x					x	x		
5830, 5840, 5860, 5870,		x							x			
6030, 6040, 6060, 6070, 6550		x							x			

Wysokość unoszenia - poziom osprzętu	2.95	3.25	3.50	3.75	4.00	4.25	4.50	2.95	3.25	3.50	3.75	4.00
Udźwig 80 cm od osi obrotu na max. wys.	1.150	1.200	1.550	1.700	2.000	2.100	2.250	950	1.150	1.450	1.600	1.850
ZAPINANIE SWORZNIOWE	Q25	Q35	Q45	Q55	Q65	Q75	Q85	Q20	Q30	Q40	Q50	Q60
6830, 6840, 6860, 6870			x	x						x	x	
6880, 7880, 8880 + Steep Nose			x	x						x	x	
7550, 7800, 8800, 7830, 7860, 7870 4 WD			x	x						x	x	
8550, 8860, 9800, 9880,			x	x						x	x	
10800, 11800				x							x	
65, 75, 85 L	x	x						x	x			