

Wysokość unoszenia - poziom osprzętu	2.95	3.25	3.50	3.75	4.00	4.25	4.50	2.95	3.25	3.50	3.75	4.00
Udźwig 80 cm od osi obrotu na max. wys.	1.150	1.200	1.550	1.700	2.000	2.100	2.250	950	1.150	1.450	1.600	1.850
ZAPINANIE SWORZNIOWE	Q25	Q35	Q45	Q55	Q65	Q75	Q85	Q20	Q30	Q40	Q50	Q60
4215, 4220, 4315, 4320		x							x			
8240, 8250 Dynashift, 8250 Powershift						x						
6110, 6120, 6130, 6140			x							x		
6150, 6160, 6170, 6180, 6190				x							x	
8110, 8120, 8130 + Dynashift				x							x	
233, 253, 254 T, 264 T, 263 T, 265, 273, 283	x	x						x	x			
274, 284, 274 S, 275 4WD, 284 S, 285, 290, 294 S		x	x						x	x		
340, 342, 352, 350, 355, 360, 353	x	x						x	x			
362, 363 T, 365, 372, 382, 373, 383, 375	x	x						x	x			
374S, 384S, 394 S + F	x							x				
377, 387, 397 + Steep Nose, 390, 393		x	x						x	x		
398, 399, 575, 590, 675, 690, 698, 699			x	x						x	x	
1004, 1007				x							x	
3050, 3060, 3065, 3065 S + Steep Nose			x							x		
3070, 3075			x	x						x	x	
3080, 3090, 3085, 3095, 3115, 3120, 3125				x							x	
3630, 3635, 3645, 3650, 3655				x							x	
3225, 3235, 3245, 3255, 3315, 3325,		x							x			
3330, 3340, 3350, 3355		x							x			