

QUICKE dla McCORMICK

Wysokość unoszenia - poziom osprzętu	2.95	3.25	3.50	3.75	4.00	4.25	4.50	2.95	3.25	3.50	3.75	4.00
Udźwig 80 cm od osi obrotu na max. wys.	1.150	1.200	1.550	1.700	2.000	2.100	2.250	950	1.150	1.450	1.600	1.850
Model ciągnika	Q25	Q35	Q45	Q55	Q65	Q75	Q85	Q20	Q30	Q40	Q50	Q60
F 75, 85, 95, 105 F / GE und XL	x							x				
MC 80, 90, 95, 100, 105, 115			x	x						x	x	
MC 110, 120, 130 Tier 3 Motor			x	x						x	x	
MC 120, 135 Power 6 (od 2008)				x	x						x	x
MTX 110, 125, 140, 155, 175, 200				x	x	x					x	x
MTX 120, 135, 150, 165, 185				x	x	x					x	x
MTX 120, 135, 150 Tier 3 Motor (od 2008)				x	x	x					x	x
XTX 145, 165						x						
XTX 185, 200, 215						x						
XTX 190, 210, 230 (od Wiosna 2008)						x						
C MAX 60	x							x				
C MAX 75, 85, 95, 105		x	x						x	x		
C MAX 75, 80, 90, 100, 105 Tier 3 Motor		x	x						x	x		
CX 75, 85,	x	x	x					x	x	x		
CX 95, 105 CX 80, 90, 105, 110 Tier 3 Motor		x	x	x					x	x	x	
CX 65 L, 75 L, 85 L	x	x						x	x			
CXL 60, 70, 80, 85 Tier 3 Motor	x	x						x	x			
C 70, 80, 90, 100		x	x						x	x		
CL 55, 65, 75, 80 (od 2008)	x	x						x	x			
ZAPINANIE SWORZNIOWE	Q25	Q35	Q45	Q55	Q65	Q75	Q85	Q20	Q30	Q40	Q50	Q60
CX 50, 60	x	x						x	x			
CX 70, 80, 90, 100		x	x						x	x		
F 70, 80, 90, 100	x	x	x					x	x	x		
F 70 L , 80 L	x	x						x	x			
F 80 XL, F 90 XL, F 100 XL		x	x						x	x		