

QUICKE dla RENAULT

Wysokość unoszenia - poziom osprzętu	2.95	3.25	3.50	3.75	4.00	4.25	4.50	2.95	3.25	3.50	3.75	4.00
Udźwig 80 cm od osi obrotu na max. wys.	1.150	1.200	1.550	1.700	2.000	2.100	2.250	950	1.150	1.450	1.600	1.850
ZAPINANIE SWORZNIOWE	Q25	Q35	Q45	Q55	Q65	Q75	Q85	Q20	Q30	Q40	Q50	Q60
Ceres 310, 65, 70 + DPS		x							x			
Ceres 75, 85, 95 + X + DPS		x	x						x	x		
Ceres 320, 330, 340 + X		x	x						x	x		
Ceres 325, 335, 345, 355 + X		x	x						x	x		
Ergos 85 - 95, Ceres 330, 340, 350, 345, 355		x	x						x	x		
Ergos 105		x	x						x	x		
Fructus 110, 120, 130, 140, Pales 210, 230, 240	x	x						x	x			
681 S, 751 S, 851 S		x	x						x	x		
58-14,65-14 LS, 70-12 LP, 70-14 LP, 75-12 LS		x	x						x	x		
75-14 LS / 80-12 , 80-14, 85-12 , 85-14 SP + LS		x	x						x	x		
58-32, 58-34, 65-32, 65-34 MA/ ME / MS / MX		x	x						x	x		
75-32, 75-34 MA/ ME / MS / MX		x	x						x	x		
61-12, 61-14 RS, 68 -12, 68-14 RS		x							x			
70-12, 70-14 F, 70-14 LB, 80-14 LB, 75-12		x	x						x	x		
75-14 RS/TS , 77-12, 77-14 RS / TS			x							x		
80-12 F, 80-14 F, 80-12, TS/TX 85-12 TS/TX			x							x		
80-14, 85-14 TS / TX			x							x		
80-32, 80-34, PA / PE / PS / PX 85-34,				x							x	
90-34 MA / ME / MS/MX/TX				x							x	
95-12, 103-12, 95-14, 103-14 RS / TS / TX					x	x						x
103 -52, 103-54 TA/TE/TS/TX					x							x
106-54,110-14, 110-54, 120-14, 120-54, 133-14,					x	x						x
133-54, 145-14, 145-54, 155-54					x	x						x