

QUICKE dla VALTRA

Wysokość unoszenia - poziom osprzętu	2.95	3.25	3.50	3.75	4.00	4.25	4.50	2.95	3.25	3.50	3.75	4.00
Udźwig 80 cm od osi obrotu na max. wys.	1.150	1.200	1.550	1.700	2.000	2.100	2.250	950	1.150	1.450	1.600	1.850
Model ciągnika	Q25	Q35	Q45	Q55	Q65	Q75	Q85	Q20	Q30	Q40	Q50	Q60
6200, 6250, 6300, 6350, 6400			x	x						x	x	
6550, 6650, 6750, 6850			x	x						x	x	
8050, 8350, 8450, 8550, 8750, 8950					x	x						x
C 90, 100, 110, 120, 130, 150				x	x						x	x
M 120, 130, 150				x	x						x	x
T 120, 130, 140, 160, 170, 180, 190					x	x						x
T 120c, 130c, 140c, 160c, 170c					x	x						x
T 170 - 190							x					
A 65- 95, 600 - 900		x	x						x	x		
N 91 - 101 + Advance *, N 82, N 92			x							x		
N 111 - 141 + Advance *			x	x						x	x	
T 121, 131, 161, 171 Classic					x	x						x
T 121, 131, 151 e, 161, 171, 191 Hi Tech					x	x						x
T 151 e, 161, 171, 191 Advance						x						
T 191 Advance							x					
ZAPINANIE SWORZNIOWE	Q25	Q35	Q45	Q55	Q65	Q75	Q85	Q20	Q30	Q40	Q50	Q60
205, 305, 405		x							x			
255, 355, 455, 555, 365, 365S, 465, 465S		x							x			
502, 504, 602, 604, 505, 605		x	x						x	x		
565, 565S, 665, 665S		x	x						x	x		
655, 705, 755, 805, 855		x	x	x					x	x	x	
715, 815			x	x						x	x	
800, 865		x	x						x	x		
600, 700, 800, 900		x	x						x	x		